

Liebert® GXT MT+

Compact Tower UPS for High Performance Power Protection
1kVA - 3kVA

Features

- Double conversion on-line technology
- Compact tower design
- Standard models and long backup models available
- Extended runtime capabilities by building up additional battery resources
- Flexible (site specific) battery configuration
- Standard model comes with internal battery
- Generator-compatible with wide input frequency range (40 to 70 Hz)
- 0.8 output power factor
- Class A electromagnetic interference (EMC)
- Ultra wide input voltage range
- High input power factor & low THDi
- Emergency power off (EPO)
- Configurable to energy saving mode (ECO)
- LCD display for operational convenience and status / fault information
- Multiple AC output interfaces via IEC standard sockets with Programmable output
- Remote Monitoring is available through USB / RS232, and optional via dry contacts and SNMP

Applications

- Small-size Data Center
- Telecommunication Equipment
- VoIP
- Small Office Network
- Computer Rooms
- Process Automation Equipment
- Network Storage Devices

The Liebert GXT MT+ features best-in-class power protection for critical applications with the use of true on-line double conversion technology.

The Liebert GXT MT+ has a comprehensive specification that provides a higher level of availability to the IT equipment. It satisfies safety criteria and electromagnetic compatibility standards while offering intelligent monitoring and network management functions. This high performance UPS with proven reliability is available in a compact tower design.



Bringing our Enterprise Level IT Expertise to your SMB

Emerson Network Power offers a full range of power protection solutions suitable for every requirement or scenario. From desktop computing, network equipment, computer rooms to large scale data centers, we make sure you get the same level of protection the Fortune 500 companies enjoy with Emerson. It is our way of Bringing Enterprise Level IT expertise to your SMB.

Desktop Computing

- Liebert PSP
- Liebert PSA
- Liebert itON BX

Network / Computer Room

- **Liebert GXT MT+**
- Liebert PSI
- Liebert GXT3

Data Center

- Liebert APM
- Liebert NX
- Liebert Hipulse



Liebert® GXT MT+

Compact Tower UPS for High Performance Power Protection
1kVA - 3kVA

Technical Specifications

Part Number	Standard Model	GXT-1000MTPLUS230	GXT-2000MTPLUS230	GXT-3000MTPLUS230			
	Long Backup Model	GXT-1000LMTPLUS230	GXT-2000LMTPLUS230	GXT-3000LMTPLUS230			
Capacity (VA/W)		1000 / 800	2000/1600	3000/2400			
Input Parameters							
Frequency Range		40Hz ~ 70 Hz					
Phase		Single phase with ground					
Power Factor		≥ 0.99 @ 220 to 230 VAC (input voltage)					
Voltage Range							
Low Line Transfer		160 VAC / 140 VAC / 120 VAC / 110 VAC ± 5 % (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)					
Low Line Comeback		175 VAC ± 5 %					
High Line Transfer		300 VAC ± 5 %					
High Line Comeback		290 VAC ± 5 %					
Output Parameters							
Output Voltage		208/220/230/240VAC					
AC Voltage Regulation		± 3% (Batt. Mode)					
Frequency Range		47 to 53 Hz or 57 to 63 Hz (Synchronized Range)					
Frequency Range (Batt. Mode)		50 Hz ± 0.25Hz					
Overload		100% to 110%: audible warning 110% to 130%: UPS shuts down in 30 seconds at battery mode or transfers to bypass mode when the utility is normal. >130%: UPS shuts down immediately at battery mode or transfer to bypass mode when the utility is normal.					
Current Crest Ratio		3:1					
Harmonic Distortion		≤ 3 % THD (Linear Load) ≤ 6 % THD (Non-linear Load)	≤ 4 % THD (Linear Load) ≤ 7 % THD (Non-linear Load)				
Waveform (Batt. Mode)		Pure Sinewave					
Efficiency							
AC Mode		~ 85%	~ 88%				
Battery Mode		~ 83%					
Transfer Time							
AC Mode to Batt. Mode		Zero					
Inverter to Bypass		4 ms (Typical)					
Battery Charger (Standard Model)							
Battery Type		12 V / 7 AH	12 V / 7 AH	12 V / 9 AH			
Numbers		3	6	6			
Typical Recharge Time		4 hours recover to 90% capacity (Typical)					
Charging Current		1.0 A(max.)					
Charging Voltage		41.0 VDC ± 1%	82.1 VDC ± 1%				
Battery Charger (Long back-up Model)							
Numbers		3	8				
Charging Current		4.0 A or 8.0 A(max.)					
Charging Voltage		41.0 VDC ± 1%	109.6 VDC ± 1%				
Physical Parameters							
Dimension, D X W X H		220 x 145 x 397	318 x 190 x 421				
Net Weight (kgs)		13	7	26	13	28	13
Environmental Parameters							
Operation Humidity		20 to 90 % RH @ 0 to 40°C (non-condensing)					
Noise Level		Less than 55dBA @ 1 Meter					
Management							
Smart RS-232 or USB		Supports Windows 98/2000/2003/XP/Vista/2008/ 7, Linux, and MAC					
Optional SNMP		Power management from SNMP manager and web browser					

Runtime (in minutes)

Load %	1000VA	2000VA	3000VA
25	38	39	31
50	17	16	12
75	10	10	7
100	6	6	4

Emerson Network Power Asia

Australia

T: 1800-065345
F: 61-2-97810252

Pakistan

T: 92-42-36622526 to 28
F: 92-42-36622530

Indonesia

T: 62-21-2513003
F: 62-21-2510622

Philippines

T: 63-2-7207400
F: 63-2-6203693

Japan

T: 81-3-54038564
F: 81-3-54032919

Singapore

T: 65-64672211
F: 65-64670130

Korea

T: 82-2-34831500
F: 82-2-5927886

Thailand

T: 66-2-6178260
F: 66-2-6178277 to 78

Malaysia

T: 603-78845000
F: 603-78845188

Vietnam

T: 84-4-37628908
F: 84-4-37628909

New Zealand

T: 64-3-3392060
F: 64-3-3392063

While every precaution has been taken to ensure accuracy and completeness herein, Emerson Network Power assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.

Emerson Network Power and Liebert® are trademarks of Emerson Electric Co. or one of its affiliated companies. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. ©2015 Emerson Electric Co.

AP15DPG-GXTMT+V3-DS

Marketing.AP@emerson.com
www.EmersonNetworkPower.Asia

EMERSON. CONSIDER IT SOLVED.™